



www.smartRdistribution.com orders@smartRdistribution.com

VR10S-MF-NGCR-VP Acre VR10S-MF NGCR - SiPass MIFARE EV1 Reader



Description

The Acre VR10S-MF NGCR SiPass MIFARE EV1 Reader is a versatile and reliable solution for access control applications. This feature-rich reader combines modern design with advanced security features, making it ideal for various environments requiring secure and user-friendly access control. Upgrade your SiPass system with the VR10S-MF NGCR and experience the benefits of enhanced security, a modern aesthetic, and a streamlined user experience.

Key Features:

- Modern and Appealing Design: The sleek and low-profile design with a black or matte chrome finish complements any building interior.
- Durable Construction: Built with a zinc casted metal bezel and polycarbonate plastic front, this reader boasts an IK08 impact rating for exceptional durability.
- MIFARE Card Technology: Provides secure and reliable access control using compatible Mifare cards (EV1 and EV2).
- Multicolour Light Frame: Offers clear visual indication of access status for enhanced user experience. The light frame can be configured to match the indicator LEDs or customised for specific access scenarios.
- Multi-Tone Buzzer: Provides audible feedback for access attempts (granted/denied).
- Easy Installation and Maintenance: The reader's simple design facilitates easy installation and maintenance.
- The VR10S can also be used with Acre SPC / Acre Intrusion systems, with the addition of an SPC OSDP Converter for VR Readers*.

*The SPC OSDP Converter ensures compatibility for the VR40S-MF 13.56 MHz Smart Card reader with the SPC/ Acre Intrusion system. This module can be inserted into SPCA210, SPCP432, or SPCP433 SPC expanders. Please select when ordering.



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	0 kg
Brand	ACRE
Power-requirement	168 mA, 8.5-30 VDC
Frequency	13.56 MHz
Output-protocol	OSDP
Operating-temperature	-40°C to 70°C
Protection-rating	IK08, IP55
Construction	Polycarbonate
Annunciation	Green LED, Red LED, Sounder, Yellow LED
Grading-compliance	Grade 3
Versions	Reader + OSDP Converter, Reader Only



Smart R Distribution Limited
Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road
Haverhill · Suffolk · CB9 7AA · England
Phone UK: 01440 704 387
Phone Int'l: +44 1440 704 387

"Putting the right pieces together"