

SR1-REX-IR500-VP

SR1-REX-IR500 Series Infrared Sensor Exit Device – available with or without over-ride switch

**Description**

Proximity technology allows remote operation of the REX function up to 10cm. Compatible with access control systems and can also be used in "stand-alone" applications. Available in two versions - with or without over-ride switch (*please select when placing your order*). The IR500 is ideal for applications where the user has their hands full or where contamination may be an issue from several people touching the same exit button. The relay is triggered when an object enters the detection field, switching the contact output to provide the REX output for unlocking the door. [caption



SR1-REX-IR500 Operation [caption]

- Material: Stainless Steel
- Finish: Brushed
- LED indicators
- Operating voltage: 12 VDC
- Current requirements: 60 mA maximum.
- Sensor range: Up to 10cm
- Contacts: Normally Open - Common - Normally Closed
- Contact rating: 3A @ 125 VAC / 30 VDC
- Relay timer period: 0.5, 5, 10 or 20 seconds (selectable)
- Nominal Dimensions: 88mm x 88mm

**Smart R Distribution Limited**

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road  
Haverhill · Suffolk · CB9 7AA · England  
Phone UK: 01440 704 387  
Phone Int'l: +44 1440 704 387

*"Putting the right pieces together"*

### Product Specifications

Weight	0 kg
Variations	,
Brand	Smart R Distribution
Colours	Brushed steel
Construction	Stainless Steel
Power-requirement	12 VDC, 60 mA
Output-relays	1
Mounting	Flush Mount