

SR1-MAG-EM150-VP

EM150 / EM150M Micro Maglock, 300Lb Holding Force, For Indoor Applications



Description

Designed for single out-swing doors. Z and L brackets are available for installation on an in-swing door, Suitable for cabinets or small doors.

- Voltage: 12 or 24VDC field selectable $\pm 15\%$
- Current: 420mA @ 12VDC (at temperature 20°C)
- Operating Temperature: -10°C to 55°C (14° to 131°F)
- Humidity: 0% to 95% non-condensing
- Holding Force: Up to 136kg (300 Lbs)
- Dual handed selectable on site
- Dimensions:
 - Magnet: 200mm (L) x 41mm (W) x 24mm (D)
 - Armature Plate: 152mm (L) x 32mm (W) x 10mm (D)
- Approximate nominal weight: 1.5kg
- **Unique Anti-Residual design:** push-off button to overcome residual magnetism and release the armature smoothly

Available in standard unmonitored and monitor-output versions - please select when ordering

Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road
Haverhill · Suffolk · CB9 7AA · England
Phone UK: 01440 704 387
Phone Int'l: +44 1440 704 387

"Putting the right pieces together"

Product Specifications

Weight	1500 kg
Brand	GEM
Holding-force	150 Lbs
Colours	Aluminium
Power-requirement	12VDC or 24VDC Selectable
Lock-options	Monitored, Unmonitored

