

KP1000  
KP1000 Standalone Keypad – 500 Users

**Description**

Vandal resistant proximity card and keypad access control unit suitable for external applications. The unit accepts up to 500 users and provides entry via PIN codes. An EM-compatible integral card reader allows optional card-entry using standard EM cards.



- Up to 500 PIN codes
- Robust metal construction
- Surface mount
- Illuminated keys
- Suitable for internal and external use
- Multi-Colour LEDs provide visual confirmation of system status
- Dry contact input for an optional external Request-To-Exit (REX) button
- Door unlock period configurable from 1 - 99 seconds
- Programming is carried out via the built-in keypad
- Power Requirements: 12VDC @ 130mA (40mA on standby)
- Two relay outputs:
  - Door relay changeover contact "NO-COM-NC" rated at 5A @ 12 VDC
  - Auxilliary relay changeover contact "NO-COM-NC" rated at 5A @ 12 VDC
- Nominal dimensions: 120mm x 76mm x 27mm
- Weight: 430g

### Product Specifications

Weight	430 kg
Brand	RGL
Frequency	125 KHz
Voltage	12 VDC
Colours	Brushed Silver
Material	Zinc Alloy
Connection-type	Terminal connection
Keypad	Illuminated Keypad, Integral Keypad
Output-relays	2
Mounting	Surface Mount
Number-of-users	500