



www.smartRdistribution.com orders@smartRdistribution.com

SR1-DG-500 DG500 Illuminated Weather-Resistant Keypad & Proximity Reader For Up To 500 Users



Description

The DG500 is a comprehensive single door access control solution that delivers exceptional security, user convenience, and weatherproof durability. This versatile system is ideal for various applications, offering a simple and effective way to manage access control for up to 500 users. With its user-friendly interface, programmable features, and robust construction, the DG500 is the perfect choice for securing your premises with confidence.

Key Features:

- Up to 500 Users: Manage access for a large number of users with
- Dual Access Methods: Provides entry via PIN codes or proximity cards/fobs for user convenience.
- Built-in Proximity Reader: Eliminates the need for separate readers, simplifying installation.
- 2 Programmable Relays: Offers flexibility for controlling door locks and other access points.
- Selectable Open Time (1-99 Seconds): Program the door unlocking duration based on your specific needs.
- Latching Mode (Optional): Keeps the door unlocked until a specific action is taken (available on auxiliary relay only).
- Vandal Resistant: Built to withstand harsh conditions and attempted tampering.
- **Tamper Sensor:** Triggers an alert if the unit is tampered with.
- Illuminated Keypad: Improves visibility in low-light conditions.
- LED Status Indication: The DG500 provides clear visual feedback on system status.
- Button Press Beep Confirmation: Offers audible confirmation for user actions.
- Cast Alloy Case (Stainless Steel Colour): Provides a sleek and durable design.



Smart R Distribution Limited

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road Haverhill · Suffolk · CB9 7AA · England Phone UK: 01440 704 387 Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



01440 704 387

www.smartRdistribution.com orders@smartRdistribution.com

Product Specifications

Weight	430 kg
Brand	Smart R Distribution
Colours	Stainless Steel
Construction	Cast Alloy
Frequency	125 kHz (RFID)
Keypad	Illuminated Keypad
Mounting	Surface Mount
Number-of-users	500
Output-relays	2
Power-requirement	12 VDC, 130 mA
Annunciation	Green LED, Red LED

