

Signo20
HID Signo Model 20 Mullion-Mount Reader

Description



HID Signo readers are available in four base models - 20, 20K, 40 and 40K. The HID Signo Reader 20 is a founding member of the Signo platform. Offering a truly dynamic approach to secure electronic access control, HID Signo Readers are designed to be highly versatile, powerful, and connected for the future. A perfect fit for door applications requiring a narrow card reader, the HID Signo Reader 20 supports a range of different credential technologies including mobile access - please select your choice when ordering. If you need assistance in identifying the correct option for your application then please contact us! Signo Model 20 is available in the following configurations (please select when ordering) :

- 20TKS-00-000000 mullion-mount multitech reader "Standard Profile", Terminal Connection
- 20NKS-00-000000 mullion-mount multitech reader "Standard Profile", Pigtail Connection
- 20TKS-01-00001H mullion-mount reader "SEOS Profile" (only reads iCLASS cards), Terminal Connection
- 20NKS-01-000000 mullion-mount reader "SEOS Profile" (only reads iCLASS cards), Pigtail Connection
- 20TKS-T2-000000 mullion-mount reader "Priority Smart Profile" (does not read 125KHz Prox), Terminal Connection
- 20NKS-T2-000000 mullion-mount reader "Priority Smart Profile" (does not read 125KHz Prox), Pigtail Connection

Product Specifications

Weight	95 kg
Brand	HID
Frequency	125 kHz (RFID), 13.56 MHz, 2.45 GHz
Mounting	Mullion, Surface Mount
Connection-type	Bluetooth, Pigtail / cable connection, Terminal connection
Colours	Black
Annunciation	Sounder, Tri-Colour LED
Operating-temperature	-35°C to 66°C
Output-protocol	Clock & Data, OSDP, Wiegand
Construction	Polycarbonate
Signo20 Variations	,

