

Signo40-VP  
HID Signo 40 – Wallswitch Reader

### Description

The HID Signo 40 is a versatile and high-performance wallswitch reader designed to enhance the security of your premises. This reader is part of the renowned HID Signo line, known for its adaptability, performance, and interoperability. With support for a wide range of credential technologies, including Seos, iCLASS, and MIFARE, the HID Signo 40 offers a seamless transition to secure authentication.

### Key Features:

- **Versatile Credential Compatibility:** Supports a wide range of credential technologies, including Seos, iCLASS, and MIFARE.
- **Enhanced Security:** Robust security features protect your access control system.
- **Remote Management:** Enables remote configuration and management for added convenience.
- **Durable Construction:** Built to withstand harsh environments and provide long-lasting performance.
- **Easy Installation:** Simple to install and integrate into existing security systems.

The HID Signo 40 is available in the following configurations (please select when ordering):

- 40TKS-00-000000 - wallswitch-mount MultiTech reader "Standard Profile", Terminal Connection
- 40NKS-00-000000 - wallswitch-mount MultiTech reader "Standard Profile", Pigtail Connection
- 40TKS-01-000000 - wallswitch-mount reader "SEOS Profile" (only reads iCLASS cards), Terminal Connection
- 40NKS-01-000000 - wallswitch-mount reader "SEOS Profile" (only reads iCLASS cards), Pigtail Connection
- 40TKS-02-000000 - wallswitch-mount reader "Smart Profile", Terminal Connection
- 40NKS-02-000000 - wallswitch-mount reader "Smart Profile", Pigtail Connection



**Product Specifications**

Weight	140 kg
Brand	HID
Frequency	125 kHz (RFID), 13.56 MHz, 2.45 GHz
Mounting	Surface Mount, Wall Mount
Connection-type	Pigtail / cable connection, Terminal connection
Colours	Black
Power-requirement	12 VDC, 250 mA
Annunciation	Sounder, Tri-Colour LED
Operating-temperature	-35°C to 66°C
Protection-rating	IP65
Output-protocol	Clock & Data, OSDP, Wiegand
Construction	Polycarbonate
Versions	Seos Profile, Smart Profile, Standard Profile
Reader-and-card-technology	AWID, Bluetooth, Mifare / Desfire CSN Only, NFC, EM Proximity (125 kHz), HID Prox (125 kHz), Indala Proximity (125 kHz), MIFARE, DESFire, HID iCLASS, HID Seos
Device-type	Reader

