

Signo40K-VP  
HID Signo 40K Reader with Keypad

### Description

The HID Signo 40K is a powerful and versatile access control reader that delivers unmatched security, convenience, and manageability. With its multi-technology compatibility, keypad functionality, and mobile-ready design, the Signo 40K is a perfect solution for organisations seeking to upgrade their access control systems with a future-proof and user-friendly solution.



### Signo Model 40K Configurations

- **Standard Profile:**

This version supports all technologies (listed below), with possible further customisation available.

- **Supported Technologies:**

- **2.4 GHz (Bluetooth):** Compatible with Mobile Credentials powered by Seos (HID Mobile Access).
- **13.56 MHz (NFC):** Compatible with Seos, iCLASS SE, iCLASS SR, iCLASS, MIFARE Classic, MIFARE DESFire EV1/EV2/EV3, and also supports Mobile Credentials powered by Seos (HID Mobile Access).
- **125 kHz:** Compatible with HID Proximity, Indala Proximity, AWID Proximity, and EM Proximity.
- **Seos Profile:** This version supports Bluetooth, NFC, and iCLASS Seos credentials.
- **Smart Profile:** This version supports Bluetooth, NFC, and 13.56 MHz credentials, including iCLASS Seos and MIFARE DESFire CSN.

**Note:** The specific configuration (Terminal or Pigtail connection, profile) of the HID Signo 40K should be chosen based on your installation needs.

**Product Specifications**

Weight	160 kg
Brand	HID
Frequency	125 kHz (RFID), 13.56 MHz, 2.45 GHz
Mounting	Surface Mount
Connection-type	Pigtail / cable connection, Terminal connection
Annunciation	Sounder, Tri-Colour LED
Operating-temperature	-35°C to 66°C
Protection-rating	IP65
Output-protocol	Clock & Data, OSDP, Wiegand
Device-type	Keypad, Reader
Reader-and-card-technology	AWID, Bluetooth, Mifare / Desfire CSN Only, NFC, EM Proximity (125 kHz), HID Prox (125 kHz), Indala Proximity (125 kHz), MIFARE, DESFire, HID iCLASS, HID Seos
Versions	Seos Profile, Smart Profile, Standard Profile

