



### www.smartRdistribution.com orders@smartRdistribution.com

# Contactless Door Release With Adjustable Sensor Range



#### Description

SR1-REX-ST200 Infra-Red Contactless Door Release With Adjustable Sensor Range.

#### **Technical Information**

- Material: Stainless Steel
- Finish: Brushed, screen printed "Door Release"
- LED "halo" door status indicator
- Rated to IP65 (sensor only)
- Operating temperature: -10°C to +70°C
- Operating voltage: 12-24 VDC
- Current requirements: 45 mA.
- Sensor range: Adjustable up to 10cm
- Contacts: Normally Open Common Normally Closed
- Contact rating: 3A @ 125 VAC / 30 VDC
- Adjustable relay timer period (0.5 -20 seconds) or toggle mode
- Nominal Dimensions: 86mm x 86mm



Smart R Distribution Limited
Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road
Haverhill · Suffolk · CB9 7AA · England
Phone UK: 01440 704 387
Phone Int'l: +44 1440 704 387

"Putting the right pieces together"



## 01440 704 387

## www.smartRdistribution.com orders@smartRdistribution.com

#### **Product Specifications**

Weight	kg
Mounting	Flush Mount, Surface Mount
Construction	Stainless Steel
Operating-temperature	-10°C to 70°C
Protection-rating	IP65 (pushbutton only)
Power-requirement	12-24 VDC