

INT-02-01-VP

Intratone Video Intercom Kit For Up To 1000 Users

**Description**

The Intratone Video Intercom Kit features a Reno SC-01 panel and is a powerful and sophisticated solution for managing access and communication in large residential or commercial buildings with up to 1000 users. This advanced system combines elegant design with cutting-edge technology to deliver seamless and secure communication.

**Key Features**

- **High Capacity:** Can manage up to 1000 users, making it ideal for large buildings and complexes.
- **Advanced Functionality:** Features a 12-button backlit coded keypad, proximity reader, and name scrolling display for enhanced user convenience.
- **Robust Construction:** Vandal and weather-resistant design ensures long-lasting performance.
- **4G-IP Connectivity:** Enables remote management and maintenance of the system.
- **Enhanced Security:** Provides secure access control with customisable settings and anti-disturbance features.
- **Stylish Design:** The Intratone Video Intercom Kit is available in three finishes to complement any building aesthetic.

Kit comprises of SC-01 door panel and 1-door controller (p/n 03-0101).

*\*Requires [12VDC 5A PSU](#) & [Transmission Unit](#) & [Export Data Per User](#).*



**Smart R Distribution Limited**

Smart R House · 13 Moonhall Business Park · Helions Bumpstead Road  
Haverhill · Suffolk · CB9 7AA · England  
Phone UK: 01440 704 387  
Phone Int'l: +44 1440 704 387

***"Putting the right pieces together"***

## Product Specifications

|                         |   |
|-------------------------|---|
| Weight                  | 0 kg  |
| Brand                   | Intratone   |
| Mounting                | Flush Mount, Surface Mount (Box Required)             |
| Power-requirement       | 12-24 VDC, 2A   |
| Operating-temperature   | -20°C to 70°C   |
| Protection-rating       | IP55  |
| Colours                 | Anthracite / Silver, Gilded / Gold, Platinum / Silver |
| Monitor-or-handset-type | App   |
| Connection-type         | GSM, Wireless   |
| Number-of-users         | 1000  |