

SR1-MAG-600ST-VP
RGL EXML600 Stainless Steel Mini Maglock For Gates

Description

The RGL EXML600 mini maglock provides a robust and user-friendly solution for gate access control. This compact unit combines a powerful holding force with a weatherproof design and flexible installation options. With its fail-safe operation and compatibility with various access control systems, the RGL EXML600 is a valuable addition to security setups for gates of all kinds. Providing up to 280Kg / 600 pounds holding force with 12VDC or 24VDC power input (selectable).

Voltage selection for the RGL EXML600 Stainless Steel Mini Maglock For Gates is made through the wiring connections during installation and an optional status monitor output version is available for systems requiring lock monitoring - please select when placing your order.

Key Features:

- **Stainless Steel Housing:** Ensures long-lasting durability and a sleek aesthetic, ideal for outdoor environments.
- **280kg (600lb) Holding Force:** Provides reliable security by delivering a strong magnetic lock on the gate.
- **Dual Voltage 12v/24v DC:** Offers compatibility with different power supply setups for flexible installation.
- **Built-in Surge Protection:** Safeguards the unit from electrical spikes and power surges.
- **Surface Mount:** Allows for straightforward installation on various gate surfaces.
- **Fail-Safe Operation:** The lock automatically disengages when power is lost, ensuring safe egress.
- **Weatherproof:** Can withstand rain, dust, and other outdoor elements for reliable operation.
- **Side or Face Fixing:** Provides installation flexibility to accommodate different gate layouts.
- **Monitored (*monitored version only*):** This version offers additional monitoring capabilities for enhanced security system integration. (Please note model selection when ordering)
- **Push-off Release Pin on Armature:** Enables manual unlocking of the gate in case of power failure.
- **Voltage Free Relay Contacts:** Allows for connection to external access control systems.



Product Specifications

Weight	2650 kg
Brand	RGL
Connection-type	Pigtail / cable connection
Construction	Stainless Steel
Holding-force	600 Lbs
Mounting	Surface Mount
Operating-temperature	-10°C to 55°C
Power-requirement	12VDC, 12VDC or 24VDC Selectable, 24 VDC
Lock-options	Monitored, Unmonitored
Form-factor	Mini Maglock, External Maglock (Stainless Steel)